



# Base Next

## Fast Allround Terminal

- Power: 32-bit Cortex-A9 processor
- Integrated signature pad
- Thermal Printing
- DCC Currency Conversion
- Environmental Resilience
- Large 4" Colour Display

## Specifications

 <b>Processor</b>	32-bit Cortex-A9   1000 MHz	 <b>Keys / Buttons</b>	Full touch display with situational adjustable keypad variants   EBS-100 compliant   10 numeric keys   5 function keys
 <b>Memory</b>	512 MB SDRAM   512 MB Flash (expandable up to 32 GB by micro SD)	 <b>Cash register Protocol</b>	ZVT, O.P.I.
 <b>Card Reader</b>	Contactless reader: ISO 14443 A/B   MIFARE   FeliCa   MasterCard contactless   Visa contactless   American Express contactless   girocard contactless   Diners contactless   UPI contactless Chip card reader: EMV L1 & L2 Magnetic stripe reader: 3 track   bidirectional	 <b>Physical</b>	181 x 83 x 72 mm   Weight: 410 g
 <b>Displays</b>	4" colour display   480 x 800 Pixel (WVGA)   Capacitive touchscreen   Integrated signature pad	 <b>Environmental</b>	Operating temp: -10°C - 50°C   Storage temp: -20°C - 70°C 10% - 93% relative air humidity   non-condensing
 <b>Comms Configurations</b>	WiFi (2,4 + 5 GHz)   LAN   RS232   USB (Host + OTG)   Bluetooth   3 x SAM (1 x SIM, 2 x SAM)	 <b>Certifications</b>	Compatible with the current specifications DK TA7.2/DC POS 3.0   EMV, RoHS, PCI-PTS 6.x   P2PE (on request)